

What is claimed is:

1. A door hinge, comprising a fixing member for  
connecting to a door, a hanger for hooking to a  
5 vertical post, an adjusting member connected to said  
hanger, and a turning member, a spring leaf, and a  
torsion spring mounted between said adjusting  
member and said fixing member; said door hinge being  
characterized in that said hanger is provided at an  
10 inner side with an upper and a lower hook, and at  
a central area with an outward raised portion, which  
is pivotally connected at a first end to one end of  
said adjusting member opposite to said door, that  
said hanger is hooked to said vertical post through  
15 engagement of said upper and said lower hook with  
hook eyes provided on said vertical post, that a  
cushion pad is positioned between said hanger and  
said vertical post, and that a tightening screw is  
threaded through said hanger to force against said  
20 cushion pad and thereby enables said upper and said  
lower hook of said hanger to firmly engage with said  
hook eyes on said vertical post, so that said door  
connected to said fixing member is pivotally mounted  
on said vertical post.

25

2. The door hinge as claimed in claim 1, wherein said raised portion of said hanger is provided at a second end opposite to said first end with a recess, and said adjusting member includes an adjusting screw having an annular groove; said adjusting screw being extended through said adjusting member with said annular groove engaged with said recess on said raised portion of said hanger, so that a clearance between said adjusting member and said hanger may be adjusted by turning said adjusting screw.

3. The door hinge as claimed in claim 1, wherein one side of said cushion pad facing toward said vertical post has a configuration corresponding to that of an outer surface of said vertical post to enable fitly and tightly bearing of said cushion pad against said vertical post.

4. The door hinge as claimed in claim 3, wherein said cushion pad is provided at predetermined positions with two through holes for said upper and said lower hook on said hanger to extend through before engaging with said hook eyes on said vertical post.